

C-PDU [4] TIS outlet, Surge Protection (Hot-swap), Master Switch & Overload Protection, LED power indicator, TIS 16A Plug, Cable 3m with 1.5 sq.mm.

Electrical	
Input connector	1 x TIS166 16 A plug
Output connectors	4 x TIS166 outlets with eyes shutter
Nominal input voltage	200-250 VAC
No. of phases	1
Acceptable input voltage	± 10% of normal voltage
Input frequency	50/60 Hz
Max. Power	3,680 W
Length of connection cable	3 m x TIS11/2553
No. of internal wires	3 (single-phase PDU)
Cable cross-section	1.5 mm ²

Physical	
Power Input	Left end single input
Bracket Install	Interchangeable L mounting brackets
Control Function	Surge Protection (Hot-swap) & Illuminated Switch with plastic cover & Overload protector with LED power indicator
Case Material	Aluminum Alloy (black)
Outlets Material	PC-ABS (red)
Insulation	Molded PVC insulation between sockets and case
Circuit Wiring Material	Industrial grade copper bar welded
Product Size (L x W x D)	437.5 x 44.4 x 56.0 mm
Shipping dimensions (L x W x D)	460.0 x 100.0 x 70.0 mm
Weight	994 g
Shipping weight	1,144 g

Environmental	
Maximum elevation (above MSL) Operating	15,000 ft (4,500 m)
Maximum elevation (above MSL) Storage	50,000 ft (15,000 m)
Temperature Operating	-5 to 50° C (23 to 122° F)
Temperature Storage	-25 to 80° C (-13 to 176° F)
Humidity Operating	5 – 95% RH non-condensing
Humidity Storage	5 – 95% RH non-condensing

Compliance	
Safety verification	VDE 0805, CE, EN 60950, IEC 60950, FCC, TIS 2432-2555
Environment verification	RoHS

PowerConneX

POWERBAR - PXC5PHTSS-TS04

C-PDU [4] TIS outlet, Surge Protection (Hot-swap), Master Switch & Overload Protection, LED power indicator, TIS 16A Plug, Cable 3m with 1.5 sq.mm.

